



Aquapure™ DF-ECO-D

Aquapure Defoamer ECO-D is a nonionic, wide spectrum defoamer consisting of highly refined components for the control and management of foam

Aquapure DF ECO-D is very effective as a Defoamer and Antifoam for many liquid processes where aeration control is needed with high shear pumping

Features & Benefits

Aquapure DF ECO-D is very cost efficient in WWT sludge processing. It has quick foam knock down and is used when persistence is needed.

Typical Applications

- Wastewater Treatment and WWT Sludge
- Latex coatings and paints
- Overprint varnishes for graphic arts
- Inks (gravure and flexographic)
- Adhesives/glues
- Paper and pulp manufacturing

Physical Data

Solubility in H ₂ O	Dispersible
Viscosity	@25 degrees C = 1000 cps
Form	Liquid
Color	Off white
Specific gravity	0.99 g/ml
pH	7-9.5

Dosing

Normal dosing ranges from 0.10% to 0.20%. For wastewater treatment effluent Aquapure Defoamer ECO-D is used at a rate of 0.05 to 0.9% / weight.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.



Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.